



## STEGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: JULY 20, 2018

### 1. PRODUCT NAME

STEGOTACK TAPE

### 2. MANUFACTURER

Stego Industries, LLC  
 216 Avenida Fabricante, Suite 101  
 San Clemente, CA 92672  
 Sales, Technical Assistance  
 Ph: (877) 464-7834  
 contact@stegoindustries.com  
 www.stegoindustries.com



### 3. PRODUCT DESCRIPTION

**USES:** StegoTack Tape is a double-sided adhesive strip used to bond and seal Stego® Wrap Vapor Barrier to concrete, masonry, wood, metal, and other surfaces. StegoTack Tape is a flexible and moldable material to allow for a variety of applications and installations.

**COMPOSITION:** StegoTack Tape is made from a blend of synthetic rubber and resins.

**SIZE:** StegoTack Tape is 2" x 50'. StegoTack Tape ships 12 rolls in a case.

### 4. TECHNICAL DATA

**TABLE 4.1: PHYSICAL PROPERTIES OF STEGOTACK TAPE**

| PROPERTY                     | RESULTS                     |
|------------------------------|-----------------------------|
| Dimensions                   | 2" x 50'                    |
| Total Thickness              | 30 mil                      |
| Permeance (30 mil)           | 0.03 perms                  |
| Color                        | Grey                        |
| Material                     | Synthetic rubber blend      |
| Adhesion to Steel            | 12.5 lb/in width ASTM D1000 |
| Installation Temperature     | 40°F/110°F                  |
| In Service Temperature Range | -20°F/+140°F                |
| VOC Content                  | No VOCs, 100% solids        |

Note: perm unit = grains/(ft<sup>2</sup>\*hr\*in-Hg)

### 5. INSTALLATION

**TO WALLS:** Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply Stego Wrap, remove the exposed release liner and press Stego Wrap firmly against StegoTack Tape to secure.

Cut StegoTack Tape using a utility knife or scissors. Cut StegoTack Tape before removing the release liner for easier cutting. Install StegoTack Tape between 40°F and 110°F. For additional information please refer to Stego's complete installation instructions.

Continued...

Note – legal notice on page 2.

## STEGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: JULY 20, 2018

### 6. AVAILABILITY & COST

StegoTack Tape is available through our network of building supply distributors. For current cost information, contact your local Stego distributor or Stego Industries' Sales Representative.

### 7. WARRANTY

Stego Industries, LLC believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego Industries does not guarantee results from the use of the information provided herein. Stego Industries, LLC does offer a limited warranty on Stego Wrap. Please see [www.stegoindustries.com/legal](http://www.stegoindustries.com/legal).

### 8. MAINTENANCE

For longer adhesive life, store in dry, temperate area.

### 9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego Industries or by visiting the website.

**Email:** [contact@stegoindustries.com](mailto:contact@stegoindustries.com)

**Contact Number:** (877) 464-7834

**Website:** [www.stegoindustries.com](http://www.stegoindustries.com)

### 10. FILING SYSTEMS

- [www.stegoindustries.com](http://www.stegoindustries.com)

